



SPECIFICATIONS

	2513	2815	3016	3212	3310	3412
Hitch Weight (lbs)	1,367	1,460	1,410	1,485	1,580	1,560
UVW (lbs)	7,898	8,174	8,853	8,593	9,998	9,990
CCC (lbs)	3,639	3,218	2,757	3,092	1,782	3,870
Exterior Length	29' 10"	32' 4"	35' 3"	36' 4"	37' 3"	38' 8"
Exterior Height	12' 1"	12' 1"	12' 1"	12' 1"	12' 1"	12' 1"
Exterior Width	102"	102"	102"	102"	102"	102"
Fresh Water (gal)	102	102	102	102	102	102
Gray Water (gal)	64	64	64	64	64	64
Black Water (gal)	32	32	32	32	32	32
Awning Size	18'	20'	20'	20'	20'	20'

CONSTRUCTED TO LAST

Our radiant-reflective insulation layers are 97% efficient keeping you comfortable all year round.

Heavy-duty Dexter® axles offer you the best in class carrying capacities.

Our Nitro-Fill™ radial tires offer a "No Excuses Guarantee" unmatched in the industry.

The XLR fully enclosed "Body Armor" underbody is insulated and uses a panel system for ease of access.

Our vacuum-bonded technology provides superior adhesion and durability.

A MOBYde® CRE3000 premium suspension smooths out over the toughest of North America's roads.

A Wide-Track frame design provides a more stable and stronger foundation over our skinnier competition.

XLR utilizes weather resistant tongue-and-groove plywood in all main living areas.

XLR has offered the strongest 5,000# tie-down anchor system in the industry since day one to secure your precious cargo.

Our 1.5" fresh water drain provides a lightning fast way to empty your tank.

